

Acid Detergent Fiber in Feeds - Filter Bag Technique (for A2000 and A2000I)

Definition

This method determines Acid Detergent Fiber, which is the residue remaining after digesting with H₂SO₄ and CTAB. The fiber residues are predominantly cellulose and lignin.

Scope

This method is applicable to grains, feeds, forages, and all fiber-bearing material.

Apparatus

1. Analytical Balance—capable of weighing 0.1 mg.
2. Oven—capable of maintaining a temperature of 102 ± 2°C (ANKOMRD Dryer, ANKOM Technology).
3. Digestion instrument—capable of performing the digestion at 100 ± 0.5°C and maintaining a pressure of 10-25psi. The instrument must be capable of creating a similar flow around each sample to ensure uniformity of extraction (ANKOM²⁰⁰⁰ with 65rpm agitation, ANKOM Technology).
4. Filter Bags—constructed from chemically inert and heat resistant filter media, capable of being heat sealed closed and able to retain 25 micron particles while permitting solution penetration (F57, ANKOM Technology).
5. Heat sealer—sufficient for sealing the filter bags closed to ensure complete closure (1915, ANKOM Technology).
6. Desiccant Pouch—collapsible sealable pouch with desiccant inside that enables the removal of air from around the filter bags (*MoistureStop* weigh pouch, ANKOM Technology).
7. Marking pen—solvent and acid resistant (F08, ANKOM Technology).

Reagents

1. Acid Detergent Solution—Add 20g cetyl trimethylammonium bromide (CTAB) to 1L 1.00N H₂SO₄ previously standardized (premixed chemical solution available from ANKOM). Agitate and heat to aid solution.
CAUTION1: Sulfuric acid is a strong acid and will cause severe burns. Protective clothing should be worn when working with this acid. Always add acid to water and not the reverse.
CAUTION2: CTAB will irritate mucous membranes. A dust mask and gloves should be worn when handling this chemical.

Sample Preparation

Grind samples in a centrifugal mill with a 2mm screen or cutter type (Wiley) mill with a 1mm screen. Samples ground finer may have particle loss from the filter bags and result in low values.

ADF Procedure (see the ANKOM²⁰⁰⁰ Operator's Manual for more detail)

1. Use a solvent resistant marker to label the filter bags to be used in the analysis.
2. Weigh and record the weight of each empty filter bag (W₁) and zero the balance. NOTE: Do not pre-dry filter bags. Any moisture will be accounted for by the blank bag correction.
3. Add 0.45 – 0.50g of prepared sample to 23 of the bags and record the weight (W₂) of each. Avoid placing the sample in the upper 4mm of the bag. Spread the sample uniformly inside the filter bag by shaking and flicking the bag to eliminate clumping.
4. Include one empty bag in the run to determine the blank bag correction (C₁). See Numbered Notes 1.
5. Using a heat sealer, completely seal each filter bag closed within 4mm of the top to encapsulate the sample. NOTE: Use sufficient heat to completely seal the filter bags and allow enough cool time (2 sec) before removing each bag from the heat sealer.
6. **Pre-extract only samples containing soybean products or >5% fat:** Extract samples by placing up to 24 bags with samples into a container with a top. Pour enough acetone into the container to cover the bags and secure the top.
CAUTION3: Acetone is extremely flammable. Avoid static electricity and use a fume hood when handling.
 Shake the container 10 times and allow bags to soak for 10 minutes. Repeat with fresh acetone. Pour out acetone and place bags on a wire screen to air-dry.
Exception – Roasted soybean: Due to the processing of roasted soy a modification to the extraction is required. Place roasted soy samples into a container with a top. Pour enough acetone into the container to cover the bags and secure the top. Shake the container 10 times and pour off the acetone. Add fresh acetone and allow samples to soak for 12 hours. After the soak time, pour out the acetone and place the bags on a wire screen to air-dry.
7. Place up to 3 bags on each of eight Bag Suspender Trays (maximum of 24 bags). Stack the trays on the center post of the Bag Suspender with each level rotated 120 degrees in relation to the tray below it. Place the empty 9th tray on top. NOTE: All nine trays must be used regardless of the number of bags being processed.
8. Verify that the hot water supply is on and the drain hose is securely positioned in the drain.
9. Read the Temperature Controller on the right side of the instrument. If the temperature is higher than 20°C, cool the Vessel as follows:
 - a. Fill the Vessel with cold water.
 - b. When the Temperature Controller reads 20°C, run the Flush Procedure to drain the water.

(procedure continued on next page)

Calculations

$$\% \text{ ADF (as-received basis)} = \frac{100 \times (W_3 - (W_1 \times C_1))}{W_2}$$

Where:

- W_1 = Bag tare weight
- W_2 = Sample weight
- W_3 = Dried weight of bag with fiber after extraction process
- C_1 = Blank bag correction (running average of final oven-dried weight divided by original blank bag weight)

Numbered Notes

1. A running average blank bag correction factor (C_1) should be used in the calculation of fiber. The inclusion of a blank bag in each run is mainly used as an indicator of particle loss. A C_1 larger than 1.0000 indicates that sample particles were lost from filter bags and deposited on the blank bag during the extraction. Any fiber particle loss from the filter bags will generate erroneous results. If particle loss is observed then the grinding method needs to be evaluated.

ADF Procedure (continued)

10. If you are using Cubetainers for your chemicals, attach the AD solution hose to the Cubetainer and then to Port B on the instrument.
11. Open the Vessel Lid and insert the Bag Suspender with bags into the Vessel and place the Bag Suspender Weight on top of the empty 9th tray to keep the Bag Suspender submerged.
12. Follow the instructions on the ANKOM²⁰⁰⁰ display:
 - a. Select ADF.
 - b. Close the Vessel Lid.
 - c. Confirm hot water is on (>70°C).
 - d. Press START.
13. When the ADF extraction and rinsing procedures are complete, open the Vessel Lid and remove the filter bags. Gently press out excess water from the bags. Place bags in a 250ml beaker and add enough acetone to cover bags and soak for 3-5 minutes.
14. Remove the filter bags from the acetone and place them on a wire screen to air-dry. Completely dry in an oven at $102 \pm 2^\circ\text{C}$. (In most ovens the filter bags will be completely dry within 2-4 hours.) NOTE: Do not place bags in the oven until the acetone has completely evaporated.
15. Remove the filter bags from the oven and immediately place them directly into a collapsible desiccant pouch and flatten to remove any air. Cool to ambient temperature and weigh the filter bags (W_3). NOTE: Do not use a conventional desiccator container.