

## Reagents

*Sulfuric acid (72% by weight)* – ANKOM Technology FSA72 or dilute reagent grade H<sub>2</sub>SO<sub>4</sub> to a specific gravity of 1634 g/L at 20°C (24.00N) by adding 1200 g H<sub>2</sub>SO<sub>4</sub> to 350 ml H<sub>2</sub>O in a 1 L MCA volumetric flask with cooling. Standardize this solution to 1634 g/L at 20°C specific gravity by removing solution and adding H<sub>2</sub>O or H<sub>2</sub>SO<sub>4</sub> as required.

## Safety Precautions (see SDS)



### WARNINGS:

Acetone is highly flammable. Use fume hood when handling acetone and avoid inhaling or contact with skin. Ensure that all the acetone has evaporated before placing in the oven.

Wear rubber gloves and face shield when handling sulfuric acid. Always add sulfuric acid to water. If acid contacts skin, wash with copious amounts of water.

## Apparatus

- a) Filtration device – ANKOM Technology – F57 Filter Bags
- b) Impulse bag sealer – ANKOM Technology – 1915 Heat Sealer
- c) Desiccator – ANKOM Technology – Desiccant/MoistureStop pouch – X45
- d) 2L & 3L Beaker

## Procedure

- 1) Grind the sample to pass through a 1 mm screen (2mm screen when using a cyclone mill).
- 2) Weigh each Filter Bag (W<sub>1</sub>), record the weight, and tare the balance.
- 3) Add 0.5 g (±0.05 g) of air-dried sample (W<sub>2</sub>) directly into each Filter Bag.
- 4) Weigh and seal one (1) blank bag and include it in the digestion to determine the blank bag correction (C<sub>1</sub>).
- 5) Seal the bags closed 4 mm from the open edge using the heat sealer.
- 6) Spread the sample uniformly inside each filter bag by flicking the bag to eliminate clumping.
- 7) Perform ADF determinations using Fiber Analyzer (See ADF Procedure).
- 8) After performing ADF determinations, place dried bags with samples into a 3 L beaker and completely cover the bags with 72% H<sub>2</sub>SO<sub>4</sub> (approximately 250 ml).

### IMPORTANT:

Bags must be completely dry and at ambient temperature before adding concentrate acid. If moisture (even ambient moisture) is present in the bags, heat generated by the H<sub>2</sub>SO<sub>4</sub> and H<sub>2</sub>O reaction will adversely affect the results.

- 9) Place a 2 L beaker inside the 3 L beaker to keep bags submerged. Agitate the bags at the start and at 30-minute intervals by gently pushing and lifting the 2 L beaker up and down approximately 30 times.
- 10) After 3 hours pour off the H<sub>2</sub>SO<sub>4</sub> and **rinse with tap water to remove all acid.**

### IMPORTANT:

If acid remains in the bags when they go into the oven, the samples will burn, resulting in values that are higher than they should be.

- 11) Repeat rinses until pH paper shows neutral color when touching the bags. Rinse with approximately 250 ml of acetone for 3 minutes to remove the water. **Handle the bags gently during rinsing. Fine lignin particles can exit the filter if not handled carefully.**
- 12) Dry the bags in an oven at 105°C for 2-4 hours.



**WARNING** – Do NOT place bags in an oven until all acetone has evaporated.


**IMPORTANT:**

When running a lignin procedure or a sequential (NDF/ADF or NDF/ADF/Lignin) with the F57 Filter Bag it is important not to dry the bags overnight after the NDF or ADF procedure. A drying timeframe of 2-4 hours at 100°C to 105°C is sufficient to thoroughly dry the bags after each procedure. Extended drying times or too high a temperature can compromise the bag's filtration media. In addition, be sure to check the water of the fourth rinse during the ADF procedure to ensure all the sulfuric acid has been removed from the bags. If litmus paper shows the presence of acid during the fourth hot water rinse, repeat until neutral.


13) Remove the bags from the oven and place them directly into Desiccant/MoistureStop pouches and flatten to remove air. Cool to ambient temperature and weigh the bags (W<sub>3</sub>).

14) Prepare each bag for the ash procedure.

14.1) Fold each bag from bottom to top. Because the bags are wider at the top than at the bottom, there will be a little extra material on each side after the first fold.



14.2) Fold each bag from right to left. The extra material now lines up on left side.



14.3) Heat seal the bag at the location of the extra material.



15) Ash the bags in pre-weighed crucibles (30 or 50 ml) at 525°C for 3 hours or until C-free. Cool and calculate weight loss (W<sub>4</sub>).

16) Calculate blank bag ash correction (C<sub>2</sub>) using weight loss upon ignition of a blank bag sequentially run through ADF and lignin steps.

17) Calculate percent ADL.

$$\text{ADL (as-received basis)} = \frac{(W_3 - (W_1 \times C_1)) \times 100}{W_2}$$

$$\text{ADL}_{\text{DM}} \text{ (DM basis)} = \frac{(W_3 - (W_1 \times C_1)) \times 100}{W_2 \times \text{DM}}$$

$$\text{ADL}_{\text{OM}} \text{ (DM basis)} = \frac{(W_4 - (W_1 \times C_2)) \times 100}{W_2 \times \text{DM}}$$

**Where:**

- W<sub>1</sub> = Bag tare weight
- W<sub>2</sub> = Sample weight
- W<sub>3</sub> = Weight after extraction process
- W<sub>4</sub> = Weight of Organic Matter (OM) (weight loss on ignition of bag and fiber residue)
- C<sub>1</sub> = Blank bag correction (final oven-dried weight/original blank bag weight)
- C<sub>2</sub> = Ash corrected blank bag (Loss of weight on ignition of bag/original blank bag)
- DM = Dry Matter